



High-Performance Solutions for Industrial Applications

W25Q-RV Series Flash Memories

Industrial Automation and Smart Home Control

Overview

Winbond's W25Q-RV series, the newly launched RV series Flash memories, combines high performance with energy efficiency for applications such as connected Internet of Things (IoT) edge devices.

Designed to serve both industrial and consumer sectors, the compact form-factor RV series reflects Winbond's commitment to innovation and meeting the evolving demands of the expanding IoT landscape. To ensure compatibility with industrial-plus grade applications, the RV series provides an operating temperature range of 105°C. Ranging from 1Mb to 32Mb, these Flash memories offer versatile solutions for diverse IoT implementations.

Density	Part Number	Datasheet	Application Note	Verilog Model	IBIS Model
32Mb	W25Q32RV	Download	Download	Download	Download
16Mb	W25Q16RV	Download	Download	Download	Download
8Mb	W25Q80RV	Download	Download	Download	Download
4Mb	W25Q40RV	Download	Download	Download	Download
2Mb	W25Q20RL	Download	Contact Us	Download	Download
1Mb	W25Q10RL	Download	Contact Us	Download	Download

Key Features

High performance of program and erase

This accelerated programming boosts factory throughput, decreases manufacturing costs, and improves efficiency.

- tPP/tSE/tBE(64KB) improves to 0.25ms/30ms/120ms

Die shrink for KGD segment and small package

This compact solution is ideal for space-constrained applications, allowing integration of Flash Known Good Die (KGD) with the System-on-Chip (SoC) in a streamlined System-In-Package (SIP) design, effectively reducing the overall footprint.

- W25Q32RV can fit in XSON2x3

Industrial plus (105°C)

The RV series ensures compatibility with demanding industrial applications, providing a robust operating temperature range of 105°C. This makes it suitable for deployment in industrial-grade environments where reliability is of utmost importance.

Excellent in XIP mode

These enhanced transfer rates empower controllers to execute code (XIP) directly from the SPI interface or accelerate boot time by shadowing code to RAM.

- STR 133MHz/ DTR 84MHz
- 84MB/S continuous data transfer rate

Fast Software Updates

Swift execution of Over-The-Air (OTA) firmware updates minimizes downtime, enhancing system availability and helping boost the end-user experience.

Longevity support

- Keep Longevity support for already MP projects.
- Encourage new design-in by using RV series to have more competitiveness

winbond

Winbond Electronics Corporation
No. 8, Keya 1st Rd., Daya Dist.,
Taichung City 428, Taiwan
Tel: 886-4-25218168
Email: mkt_online@winbond.com

Winbond Electronics Corporation America
2727 North First Street,
San Jose, CA 95134, U.S.A.
Tel: 1-408-943-6666



www.winbond.com